



TOP PROTECTION FOR EVERY WELDER

Autodarkening welding helmet with an advanced air distribution systems for increased user's comfort and respiratory protection without compromise.

Verus air is a professional welding helmet suitable for most of welding processes such as MIG/ MAG, SMAW, TIG, Plasma Arc welding and cutting, Carbon Arc gouging, gas welding and cutting. Not suitable for laser welding.

- The highest respiratory protection and more comfort thanks to an advanced built-in air distribution system
- True colour ADF with the highest optical quality 1/1/1/1
- Fast and easy replacement of all spare parts

CleanAIR® Verus Air

AIR DISTRIBUTION

An advanced built-in air distribution system......

EASY SWITCH

TILT ANGLE CONTROL

The tilt adjustment knob is easily accessible from the outside of the helmet.

FULLY ADJUSTABLE

Outer control of the direction and intensity of the air in the helmet.

ICUTWEIGHT AND DUDADLE

Lightweight and durable shell, meets the requirements of EN 175 B and thus ensuring protection against high speed particles.

Compatible powered air purifying respirators / airline systems

AerGO®



Basic



Chemical 2F



Pressure Flow Master



Pressure



VariGEAR

CleanAIR®

FITS ALL HEAD SHAPES

Newly designed head suspension allows multiple individual settings.

SOFT PADDINGS

The soft padding sits gently on the top of the head and ensures better weight distribution and a perfect fit.

COMFOTABLE HEADGEAR

The crown part of the headgear is vertically adjustable to fit all head shapes and sizes.

QUICK REPLACEMENT

Easy replacement of the headgear just by sliding it out of the holder.

CUSTOMIZADIE

Easy adjustment of the distance between the face of the welder and ADF.

Keep the helmet as close as possible to your eyes for a wider view and minimum neck strain.

PRECISE FIT

The smooth ratchet
mechanism allows
precise adjustment
of the head
circumference
and a secure fit.

HORE HOLDER

Easily removable hose holder can be placed either left or right.

COMFORT FOR YOUR HEAD

The soft padding of the back part of the headgear swivels to fit different head shapes.

Adjustable air flow



For more individual comfort you can regulate the airflow in three zones

Zone 1 – control lever, accessible from outside the helmet, controls the direction of the air coming from the lower part of the airduct.

Zone 2 – control knob, accessible from outside the helmet, controls the air coming from the upper part of the airduct.

Zone 3 – the two sliders on the inside of the the helmet control the intensity of the airflow coming either towards welder's mouth or from the sides.

ADF S60+





True colour display for increased colour perception and excellent clarity of vision at all time.

Large viewing area 98 x 62 mm

- Superb optics for a better view
- Ten available dark shades for various welding jobs
- The delay function allows the user to set the switching time from dark to light
- A wide range of sensitivity settings allow the welder to adapt the ADF to all welding processes
- Four sensors for stable arc detection
- Smart power control auto ON, auto OFF (after 30 min if not in use)
- Magnifying lens can be easily attached to the ADF
- Meeting the highest requirements according to EN 379 for eye protection of welders

Extend your protection

available accessories*

Protective head cover, flame retardant 70 30 71 Protective neck cover, flame retardant 70 30 72







VERUS air

Helmet technical specifications

793 g
Polyamide (PA)
QuickLOCK™
powered air purifying respirators - EN 12941, TH3 / NPF 500
airline sytems (supplied air) - EN 14594 (3B) / NPF 200
welding helmet - EN 175 B
welding filter - EN 379 (1/1/1)

ADF technical specifications

110 x 90 x 7 mm
98 x 62 mm
dark state, variable 5-8 / 9-14
light state 3
0,00015 s (0,15 ms) - light to dark
0,1 - 0,9 s (adjustable) - dark to light

Product name	Product code
Welding helmet CleanAIR® Verus air, incl. ADF S60+	70 30 01
Ready 2 Weld - CleanAIR® AerGO® & Verus air	30 30 01
Ready 2 Weld - CleanAIR® Basic & Verus air	81 30 01



MALINA – Safety s.r.o. Luční 1391/11 | 466 01 | Jablonec nad Nisou Czech Republic Tel.: +420 483 356 600 | export@malina-safety.cz