



flofloor


BASIC & CREATIONS TILES COLLECTION

Basic & Creations collection - tile samples

What is Flofloor?

Flofloor flooring has added a completely new dimension to flooring solutions. It combines the advantages of a warm and comfortable carpet flooring and of a durable PVC flooring that is resistant to wearing away. Flofloor collection comprises a wide variety of melange tiles in terms of colour and shape which will soon also include 3D and imprinted tile collections. Moreover, Flofloor collection is complemented with foamed PVC skirting boards that are flocked with the same fibres. The possibility to heat bend the skirting boards to fit angles highly facilitates their installation. In addition to that, their flexibility enables easy fitting to curved walls or pillars.

In terms of standard of cleanliness, the lack of loops and weaves that could retain deep-seated dust is an added advantage of Flofloor tiles. Thanks to thick, 22dtex polyamide fibres dust and house dust mite can be easily and quickly removed. What is more, the anti-static properties of the flock coat further facilitate dust particle removal. Flofloor flooring dimensions are perfectly maintained owing to the base used and the velour-like look of the floor is achieved thanks to polyamide fibres. Furthermore, Flofloor highly reduces noise levels and protects against slipping.



Designed to last for years

A base made from LVT flocked with polyamide fibres (70 million fibres per square meter) is a uniform, damp-proof and waterproof product. Almost vertical arrangement of fibres that are applied using an electrostatic attraction method prevents any permanent deformation resulting from the moving wheels of chairs or armchairs. At the same time, since Flofloor is not too soft, it does not obstruct the movement of office swivel chairs. Thanks to such properties Flofloor is perfect for office and hotel spaces that require combining elegance, durability and easy maintenance.

Comfort and safety

The technology of bonding polyamide fibres with LVT base improves comfort at work thanks to its highly effective noise dampening properties. In addition to that, its features eliminate the risk of stumbling or slipping on either dry or wet surface.


Easy maintenance

The quality of a fitted carpet combined with the ease of maintenance of a PVC flooring. Thanks to following the manufacturer's cleaning instructions, Flofloor flooring will look brand-new for years. The properties of polyamide fibres facilitate removal of any, even stubborn stains while maintaining the colour and physical parameters. Thanks to smooth surface and straight shape of the polyamide fibres which prevent retention of dust and dirt, it is easy to vacuum Flofloor and the vacuum cleaner can reach the very base of the fibres. Any fresh stains can be removed with the use of a damp sponge and a bit of soap and washing-up liquid, if necessary, whereas already dried stains can be removed using appropriate chemical agents that are intended for cleaning flooring. Flofloor can be either dry or wet cleaned using steam cleaners or wet vacuum cleaners.

Basic & Creations collection colours



10005 Sorbet Cytrynowy/ Lemon Sorbet



20003 Piasek / Sand



20018 Czekolada / Chocolate



20032 Aluminium / Aluminium



10010 Melonowy Róż/ Melon Pink



20005 Cappuccino / Cappuccino



20020 Trawa / Grass




20035 Granit / Granite



10015 Lody truskawkowe/Strawberry ice-cream



20007 Toffi / Toffee



20023 Szmaragd / Emerald



20038 Stal / Steel



10020 Biała Limonka/Pale Lime




20010 Cegła / Brick



20028 Niebo / Sky



20042 Bazalt / Basalt




10025 Zimowy Błękit/ Frost Blue



20013 Makowy / Poppy



20030 Ocean / Ocean



20048 Antracyt / Anthracite



10030 Pustynny Beż/Desert Beige



30005 Przyciemniony Łosoś/Muted Salmon



30035 Kwiatowy Odcień/Blossom Shade



30105 Nasycona Wiśnia/Saturated Cherry



30135 Cień Malwy/Mauve Shadow



30010 Subtelny Róż/Subtle Pink



30040 Wiosenna Ziemia/Spring Ground



30101 Cynober/Vermillion



30140 Kawowy Onyks/Coffee Onyx



30015 Białe Płatki/Pale Petal



30045 Niebieska Mięta/Blue Mint



30115 Stare Wino/Old Wine



30145 Północny Las/Northern Forest



30020 Pastelowa Brzoskwinia/Pastel Peach



30050 Burzowe Niebo/Stormy Sky



30120 Palona Sienna/Burnt Sienna



30150 Atramentowa Zieleń/Ink Green



30025 Światło Świtu/Dawn Glow



30055 Alaskańska Zieleń/Alaskan Green



30125 Ciepły Piernik/Warm Gingerbread



30155 Kamień Pruski/Prussian Stone



30030 Delikatna Brzoskwinia/Tender Peach



30060 Nordycki Poranek/Nordic Morning



30130 Śliwka Cukrowa/Sugar Plum



30160 Północny Błękit/Midnight Blue



















Properties

Comfortable as a carpet flooring and easy to clean as a PVC flooring.

Flofloor advantages and features:

- Complementary system consisting of flooring and skirting boards that are flocked with fibre
- A few times more fibres per square metre than a carpet flooring
- Fully resistant to moisture, flooding and mould
- Durable and stable dimension-wise
- Dry or wet cleaned using standard cleaning equipment
- Smooth velour-like surface adding warmth and soundproofing properties
- Anti-slip, anti-static and anti-reflective properties
- Fire-retardant
- Conventional installation, like the one applicable to LVT panels
- Easy demounting of damaged tiles, if any
- Dust and dust mite is simply vacuumed
- Easily removed stains with a wet sponge or applicable cleaning agents
- Heat bending and glueing to walls
- The only skirting boards flocked with polyamide fibre available

Technical specifications

| | Specification | Standard | Tile |
|---|---------------------------|-----------------|---------------------------------------|
|  | Commercial flooring | EN-ISO 10874 | Class 33 |
|  | Fibre type | ISO 1765 | 100% Poliamid 6.6; 22 dtex; 2 mm long |
|  | Total thickness | | 3,8 mm |
|  | Tile size | | 500 mm x 500 mm |
|  | Total weight | ISO 8543 | 5,20 kg/m ² |
|  | Panels per box | | 20 pcs; 5 m ² ; 27 kg |
|  | Dimensional stability | ISO2551/EN986 | ±0.12 mm (457 mm;457 mm) |
|  | Colourfastness | EN-ISO 105-B02 | ≥ 6 |
|  | Slip resistance | EN 13893 | Very low risk DS: ≥ 0.30 |
|  | Impact sound insulation | EN ISO 717-2 | ΔL _w ≥ 19 dB |
|  | Sound absorption | ISO 354 | α _w = 0,10 (H) |
|  | Castor chair resistance | EN 985 Test A | r ≥ 2,4 castor chair continuous use |
|  | Wear classification | EN 1307 Annex F | >1000 cycles |
|  | Comfort class | | 5 |
|  | Fire rating | EN 13501 | BFI-s1 |
|  | Watertightness | EN 1307 Annex G | Waterproof |
|  | Electrostatic propensity | ISO 6356 | < 2 kV |
|  | Underfloor heating system | ISO 8302 | 0,037 m ² K/W |